

Liquid crystal display method and device for improving quality of cartoon pictures

Patent number: CN1279459

Publication date: 2001-01-10

Inventor: HIROICHI MIYAJI (JP)

Applicant: SHARP KK (JP)

Classification:

- international: G09G3/36; G09G5/36

- european: G09G3/34B; G09G3/36C8; G09G3/36C12A;
G09G3/36C14A

Application number: CN20000124109 20000615

Priority number(s): JP1990168152 19990615; JP20000125910 20000426

Also published as:

EP1061499 (A2)
US6937224 (B1)
US2005237294 (A1)
JP2001060078 (A)
EP1061499 (A3)


more >>

Report a data error here

Abstract not available for CN1279459

Abstract of corresponding document: **EP1061499**

A source driver 12 outputs a data signal and a reset (black) signal alternately to a source line S. Four-hundred and eighty gate lines G are divided into three groups each comprising 160 lines, and connected to gate drivers 13a - 13c. A display control section 20 outputs a discriminant signal, a scan start signal and a clock signal to the gate drivers 13, where the nth gate line G is selected with the data signal outputted by the source driver 12, and where the (n+160)th gate line G is selected with the reset signal outputted. Further, n is shifted sequentially. By writing the reset signal during the latter 1/3 of one frame like this, light leakage of pixels that are changed over from white display to black display is eliminated. Also, blurs of edge portions of a motion picture are reduced. Thus, display grade for motion pictures is enhanced with a minimum improvement.



Data supplied from the esp@cenet database - Worldwide

D1

[19] 中华人民共和国国家知识产权局

[51] Int. Cl⁷

G09G 3/36
G09G 5/36

[12] 发明专利申请公开说明书

[21] 申请号 00124109.5

[43] 公开日 2001 年 1 月 10 日

[11] 公开号 CN 1279459A

[22] 申请日 2000.6.15 [21] 申请号 00124109.5
[30] 优先权
[32] 1999.6.15 [33] JP [31] 168152/1999
[32] 2000.4.26 [33] JP [31] 125910/2000
[71] 申请人 夏普公司
地址 日本大阪市
[72] 发明人 宫地弘一


[74] 专利代理机构 中国专利代理(香港)有限公司
代理人 王忠忠

权利要求书 6 页 说明书 26 页 附图页数 19 页

[54] 发明名称 液晶显示方法和改进动画显示质量的液晶显示装置

[57] 摘要

一个源极驱动器 12 把数据信号和复位(黑电平)信号交替地输出给一个源极线 S。把 480 条控制线 G 分成 3 组,使每组由 160 条线组成,三组控制线分别与控制极驱动器 13a-13c 相连。显示控制单元 20 把识别信号、扫描开始信号和时钟信号输出给控制极驱动器 13,通过源极驱动器 12 输出的数据信号选择第 n 个控制线 G,并通过输出复位信号选择第(n+160)控制线 G,另外,顺序移动 n。



ISSN 1008-4274

知识产权出版社出版